

EAS System

Radio Frequency Technology

ZKRF10M

ZKRF20M



ZKRF10M



ZKRF20M

Features

- Anti-interference from metal
- Advance digital signal processing technology
- Stable structure ensures long-lasting durability
- Suitable for wide entrance
- Environmentally friendly

Specifications


Model	ZKRF10M	ZKRF20M
Operating Voltage	AC110 ~ 220V, 50 ~ 60hz	AC110 ~ 220V, 50 ~ 60hz
Rated Power	≤15W	≤15W
Center Frequency	8.2Mhz	8.2Mhz
Working Mode	TX + RX	TX + RX
Detection Range	0.9 ~ 2M (Depend on tag)	0.9 ~ 2.4M (Depend on tag)
Main Material	Aluminum Alloy	Aluminum Alloy
Appearance Size (mm)	1580 * 380 * 30	1570 * 440 * 40
Packing Size (mm)	1630 * 440 * 210	1630 * 520 * 190
Packing Unit	2pcs / ctn	2pcs / ctn
Packing G.W.	11.5kgs / ctn	13.5kgs / ctn

Consumable

ZKRF10M & ZKRF20M Deactivator



EAS-769B:
RF Plastic Deactivator



EAS-D01:

Normal Detacher 4500GS



EAS-D10N:

Universal Detacher 10000GS

ZKRF10M & ZKRF20M Electronic Tag



EAS-H01:
Small Square



EAS-H02:
Big Square



EAS-L404:
RF Soft Label
40 * 40 (mm)



EAS-H22C:
Bottle Tag



EAS-H23:
Milk Can Tag



EAS-301:
Spider Tag



EAS-H14A:
Tag with Lanyard

