

Vcare-10 4G

WiFi + 4G Smart Burglar Alarm Gateway

*Real-time intrusion alerts to your phone & monitoring center
— dual connectivity, zero blind spots*



The Patrol Hawk Vcare-10 4G is a cloud-connected smart alarm gateway that transmits intrusion, SOS, smoke, and gas leak alerts via WiFi or 4G LTE directly to security monitoring centers and user mobile phones. Designed for professional burglar alarm deployments, it supports wireless sensor integration, remote arming/disarming, and real-time video access — making it the ideal hub for banks, commercial buildings, and residential security networks.



Recommended for **Bank Branch Security** — supports 24/7 monitoring center integration, silent alarm relay, and dual-path redundancy required for financial-grade installations.

KEY FEATURES

- ✓ **Dual-Path Alarm Transmission** — sends alerts via WiFi and 4G LTE simultaneously — no single point of failure
- ✓ **Multi-Threat Detection** — supports intrusion, SOS emergency, smoke fire, and gas leakage sensor inputs
- ✓ **Instant Mobile Notification** — pushes real-time alarm alerts to user smartphones and CMS monitoring center
- ✓ **Remote Arm / Disarm** — full remote control and configuration from mobile app or central monitoring software
- ✓ **Live Video Verification** — connects to IP camera for real-time visual verification on alarm trigger
- ✓ **Wireless Sensor Ecosystem** — works with door detectors, PIR motion sensors, emergency buttons, and more

APPLICATIONS

- Banks & Financial Institutions
- Corporate Offices & Commercial Buildings
- Retail Stores & Shopping Malls
- Hospitals & Healthcare Facilities
- Hotels & Residential Complexes
- Industrial Sites & Warehouses

TECHNICAL SPECIFICATIONS

Model	Vcare-10 4G	Product Type	Smart Alarm Gateway
Connectivity	WiFi 802.11b/g/n + 4G LTE	WiFi Standard	802.11b/g/n (2.4GHz)
4G LTE Bands	Multi-band, global coverage	SIM Card Slot	Standard SIM
Ethernet Ports	2× RJ45 (10/100 Mbps)	Antenna	Dual external (WiFi + 4G)
Alert Types	Intrusion / SOS / Smoke / Gas	Notification	Mobile App + CMS Center
Remote Control	App / Web Dashboard / API	Power Supply	9–24V DC (wide range)
Power Consumption	<5W idle / <15W active	Operating Temp.	-10°C to +55°C
Humidity	5%–95% non-condensing	Dimensions	210 × 140 × 45 mm
Weight	Approx. 350g	Warranty	24 Months

CERTIFICATIONS

CE

FCC

RoHS

PATROL HAWK

The professional manufacturer of alarm system, since 2003

AUTHORIZED DISTRIBUTOR

DIGI-MARK SOLUTION
Authorized Bangladesh Partner
www.digimarkbd.com

CONTACT

info@digimarkbd.com
+880 1979-234342
Rahmania Int'l Complex (1st Floor)
28/1/C, Toyenbee Circular Road
Motijheel, Dhaka-1000, Bangladesh